



Corner	Bearing	Distance	Remarks
A.			
B.	Beech	20	N 70 W 12 1/2
	Hickory	18	S 78 E 16 1/2
C.	Sugar	10	S 70 E 23
	Lilac	10	S 84 33
D.	W. ash	9	west 83
	Do	12	N 13 W 75
E.	B. oak	10	N 68 E 17
	W. oak	8	S 82 E 12
F.	Hickory	8	west 3
	W. oak	8	N 18 E 9
G.	Walnut	6	S 68 W 97
	Dogwood	4	N 75 W 18
H.	Sarvice	3	S 61 W 2
	C. oak	15	S 12 W 9
I.	B. oak	8	East 10 1/2
	Beech	6	N 56 E 18 1/2
K.	Maple	10	S 47 E 22
	elm	14	N 15 E 13 1/2
L.	B. oak	12	S 44 E 13
	Beech	5	S 75 W 21
M.	Hickory	12	North 6 1/2
	elm	8	N 17 W 28 1/2
N.	H. Oak	18	S 54 W 35
O.	W. oak	20	S 46 1/2 W 32 1/2
P.	Sugar	18	S 80 E 64 in a Road
	W. oak	18	North 11 3/4
Q.	Hickory	8	S 21 E 11
	Hickory	15	S 86 W 13 1/2
R.	Do.	9	N 16 E 24
S.	B. oak	14	S 74 W 16
T.	Sour gum	8	S 45 E 16 1/2
	W. oak	18	S 2 W 16 1/2
U.	N. E. corner		
	of course		S 29 W 76.

I here by Certify the Above to be a true correct Plat of Fractional Lots in Section No. 12 Township No. 13 Range No. 13 Locking County Ohio Surveyed 1870. By Levi Davis Surveyor.

Rec'd and Recorded Nov. 14" 1883.

Jacob. Kearse Recorder.

The Above Plat transferred from Plat Book "A" page 4 + 5 Record of Fractional Lots S.C.C. July 15" 1901. and Certified to be a true copy by P. H. Sloan Recorder S.C.C.